

# HL-10 EXPLORER

H-Series

## MULTI-USE RECHARGEABLE HEADLAMP SYSTEM

The HL-10 is a high performance headlamp with two separate light apertures. The first aperture (Mode 1) is the 2500 lumen main lamp w/ 4 light settings, SOS, and strobe. The second aperture (Mode 2) emits a diffused red light, diffused white light and an IR 850nm light for use with night vision equipment. The Mode 2 lights can also be run either in the constant on, strobe or SOS modes. The HL-10 is rechargeable via magnetic USB cable and uses the "J" mount system for attachment to the included headband or to other compatible mounts.

- J-HOOK BUCKLE ATTACHMENT SYSTEM
- MAGNETIC CHARGING
- FLOOD / DIFFUSED LIGHT MODE
- FOCUSED LIGHT MODE



### MULTI-COLOR OUTPUT

#### FOCUSED LIGHT (MODE 1) ILLUMINATION FUNCTIONS

Mode:	Low	Medium	High	Turbo	Strobe	S.O.S.
Max Output:	20 lm	300 lm	1180 lm	2500 lm	2500 lm	2500 lm
Runtime:	2.78 days	4.95 hrs	1.6 hrs	1.53 hrs	2 hrs	2 hrs





#### FLOOD / DIFFUSED LIGHT (MODE 2) ILLUMINATION FUNCTIONS

Mode:	On	Strobe	S.O.S.
White Output:	150 lm	150 lm	150 lm
White Runtime:	6.4 hrs	12.8 hrs	12.8 hrs
Red Output:	625 nm	625 nm	625 nm
Red Runtime:	7 hrs	14 hrs	14 hrs
IR Output:	850 nm	850 nm	850 nm
IR Runtime:	9.75 hrs	19.5 hrs	19.5 hrs

Battery: (1) 18650-3200 mAh High Discharge Rechargeable Li-ion.  
NOT compatible with RCR123A/16340

Size: Length: 79 mm  
Width: 24.5 mm  
Height: 49.5 mm

Weight: 111g (without battery and straps)



All performance data are results of testing to ANSI / NEMA FL1-2019 Standards

#### KIT INCLUDES

- (1) HL-10 HEADLAMP
- (1) MAGNETIC CHARGE CABLE
- (1) 18650-3200 mAh HIGH DISCHARGE LI-ION BATTERY
- REPLACEMENT O-RINGS

